



Comparison Chart

DSI-HS10B FABRIC FIRE CURTAIN vs. ROLLING STEEL FIRE DOORS

| Features & Qualifications | DSI-HS10B HOSE STREAM RATED SMOKE AND FIRE CURTAIN | Overhead Coiling Steel Fire Doors |
|-------------------------------|--|--------------------------------------|
| Fire Label | UL 10B with Hose Stream | UL 10B with Hose Stream |
| Fire Rating | 20, 90, or 180 minutes | 20, 90, or 180 minutes |
| Smoke Label | UL 1784 (Standard) | UL 1784 (Optional)* |
| Smoke Seals | Not Required | Required for "S" Label |
| Fail Safe Operation | Standard | Optional for an added cost |
| Minimum Head Room Requirement | 9" | 16" |
| Maximum Head Room Requirement | 12" | 30" |
| Side Clearance Required | 4" on all sizes | Varies from 7 1/2" - 13 1/2" |
| Weight | 3-5 lbs. per Sq. Ft. | 13-15 lbs. per Sq. Ft. |
| Maximum Opening Size | 984' Wide x 26' Tall* | 24' Wide x 24' Tall* |
| Activation Function | Fire Alarm &(or) Fusible Link | Fire Alarm &(or) Fusible Link |
| Auto Reset Function | Standard | Optional for an added cost |
| Egress | Multiple options available | Not available |
| Battery Back-up | Standard | Optional for an added cost |
| Power Requirements | 24V standard | 120V Minimum |
| Finishes | Factory Primed finish | Factory Primed finish |

* Contact Factory for options or other sizes