

CERTIFICATE OF COMPLIANCE

Certificate Number 20220406-R39636
Report Reference R38702
Issue Date 2022-April 06

Issued to: Door Systems Inc
1150 Las Brisas Pl
Placentia, CA 92870 USA

**This certificate confirms that
representative samples of**

Fire-protective Curtains

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 10D, "Fire Tests of Fire Protective Curtain Assemblies."
UL 1784, "Air Leakage Tests of Door Assemblies."

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

See addendum pages 2-3.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20220406-R39636
Report Reference R38702
Issue Date 2022-April 06

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model(s) below are for use in gypsum or masonry wall type constructions, maximum 3657 mm (144 in.) wide by 3048 mm (120 in.) high. When greater than 3657 mm (144 in.) wide by 3048 mm (120 in.) high, the single barrel and multibarrel assemblies are eligible for the Oversized Label and may be produced up to 6 m (19.7 ft.) wide by 12 m (39.4 ft.) high and up to 300 m (984.3 ft.) wide by 12 m (39.4 ft.) high, respectively.

Fire-protective curtain:

DSI-C1HRS Smoke and Fire Curtain, 1 hr fire rating.

DSI-600S1 Elevator Smoke Containment System, 1 hr fire rating

DSI-C1HRM Smoke and Fire Curtain, 1 hr fire rating.

DSI-600M1 Elevator Smoke Containment System, 1 hr fire rating.

DSI-C3HRS Smoke and Fire Curtain, 3 hr fire rating.

DSI-600S3 Elevator Smoke Containment System, 3 hr fire rating.

DSI-C3HRM Smoke and Fire Curtain, 3 hr fire rating.

DSI-600M3 Elevator Smoke Containment System, 3 hr fire rating.

DSI-D1HRS Automatic Smoke Draft Curtain, 1 hr fire rating.

DSI-D1HRM Automatic Smoke Draft Curtain, 1 hr fire rating.

DSI-D3HRS Automatic Draft Curtain, 3 hr fire rating.

DSI-D3HRM Automatic Draft Curtain, 3 hr fire rating.

Model(s) above may have suffix "E" for egress option.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20220406-R39636
Report Reference R38702
Issue Date 2022-April 06

Model(s) below are for use in masonry or gypsum wall type constructions, maximum 3657 mm (144 in.) length by 3048 mm (120 in.) high. When greater than 3657 mm (144 in.) length by 3048 mm (120 in.) high, the assembly is eligible for the Oversized Label and may be produced up to 250 m (820.2 ft.) length by 12 m (39.4 ft.) high.

Fire protective curtain:

DSI-A1HR Accordion Smoke and Fire Curtain, 1 hr fire rating.

DSI-A4HR Accordion Smoke and Fire Curtain, 4 hr fire rating.

Model(s) below are for use in masonry floor type constructions, maximum 10000 mm (394 in.) travel by 8000 mm (315 in.) wide and maximum 8000 mm (315 in.) travel by 10000 mm (394 in.) wide.

Fire protective curtain:

DSI-H1HR Horizontal Fire Curtain, 1 hr fire rating

DSI-H3HR Horizontal Fire Curtain, 3 hr fire rating

DSI-H1HR Horizontal Fire Curtain, 1 hr fire rating Oversized.

DSI-H3HR Horizontal Fire Curtain, 3 hr fire rating Oversized.

The products below have been additionally investigated to ANSI/UL 1784

Fire-protective curtain:

DSI-C1HRSS Smoke and Fire Curtain, 1hr fire rating

DSI-C1HRSM Smoke and Fire Curtain, 1hr fire rating

DSI-C3HRSS Smoke and Fire Curtain, 3hr fire rating

DSI-C3HRSM Smoke and Fire Curtain, 3hr fire rating

DSI-D1HRSS Automatic Draft Curtain DSI-D1HRSM Automatic Draft Curtain

DSI-D3HRSS Automatic Draft Curtain DSI-D3HRSM Automatic Draft Curtain



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20220406-R39636
Report Reference R38702
Issue Date 2022-April 06

DSI-A4HR Accordion Smoke and Fire Curtain, 4 hr fire rating

DSI-A1HR Accordion Smoke and Fire Curtain, 1 hr fire rating

DSI 600S1 Elevator Smoke Containment System, 1hr fire rating

DSI 600M1 Elevator Smoke Containment System, 1hr fire rating

DSI 600S3 Elevator Smoke Containment System, 3hr fire rating

DSI 600M3 Elevator Smoke Containment System, 3hr fire rating



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

